

# **DEER FENCE INSIDE END KIT- 2 PACK**

PIPE PARTS LIST						
6' END DE2522-60		2.5 <sup>5</sup> Planeter		1.5/8"		
	2 ½" x 9' Black Coated Galvaniz		1 5/8" x 7'Black Powder Coated			
			Galvanized Pipe			
7.5' END	DE8362-108	Qty: 2	DE8358-084	Qty: 2		
DE2522-75		2.5" Diameter		1.5/8"		
	2 ½" x 9' Black Powder Coated Galvanized Pipe		1 5/8" x 9'Black Powder Coated Galvanized Pipe		2 ½" x 24" End Extension	
	DE8362-108	Qty: 2	DE8358-108	Qty: 2	DE8166	Qty: 2
8' END		2.5"		1 5/8"		
DE2522-80		Dameer				
	2 ½" x 9' Black Coated Galvani		1 5/8" x 9'Black Powder Coated Galvanized Pipe		2 ½" x 24" End Extension	
	DE8362-108	Qty: 2		Qty: 2	DE8166	Qty: 2





HARDWARE PARTS LIST						
	×					
1 5/8" Brace Cup- Black	2 ½" Brace B			ack	5/16" x 1 1/ Galvanized Bolt, Nut 8	d Carriage & Washer
DE8144 Qty: 2	DE8084	Qty: 2	DE8091	Qty: 2	DE8042	Qty: 2
∛″ Self-Tapping Screw						
(Not Incl. in 6' Corner)						
DE8450 Qty: 4						





## Step 1:

For 6' end systems, insert the 2  $\frac{1}{2}$ " post cap in one end of the 2  $\frac{1}{2}$ " diameter vertical corner post, then proceed to step 2.

**For 7.5' and 8' end systems:** Insert the 2 ½" post cap into the black end of the 2 ½" x 24" corner post extension. Slide the silver end of the end post extension into one end of the 2 ½" vertical end post. Secure the extension using 2 self-tapping screws approx. 1" down from the top of the 9' vertical post. You can drill pilot holes in the post using a 1/8" drill bit, if necessary.



## Step 2:

Locate the position on the fence line where you are placing your end post. Use a shovel or post hole digger to create a hole for the  $2 \frac{1}{2}$ " vertical end post according to the following depth guide.

End Height	Hole Width	Hole Depth
6' Corner	12"	36″
7.5' Corner	14"	42″
8' Corner	14"	36″

Place the 2 ½" diameter vertical end post in the hole, with the extension at the top, and either set in concrete (Preferred) or back fill with dirt and tamp firmly. Setting the posts in concrete will strengthen the overall system and provide support for the deer fence system over a longer period. When using concrete be sure to let the concrete set completely before proceeding to Step 3.





For questions or technical support call 888-422-3337



### Step 3:

If using tensioning, first slide one monofilament alignment band over the post and to the bottom. Slide brace bands down the 2 ½" vertical end post until they are approximately 12" from the top of the vertical corner post. Attach the brace bands using the supplied bolts, nuts and washers. Do not fully tighten the nuts until the final placement of the brace posts is complete.



#### Step 4:

Insert brace post into the brace cup. Position the other end of the brace post so it contacts the ground just inside the eventual fence line. The brace post should be resting on the ground at about a 45-degree angle from the end post.



Dig a hole 1' deep where the brace post contacts the ground. Place a dead man (cinder block, large brick, or stone) in the hole perpendicular to the brace post. Wedge the brace post against the block to provide support for the vertical end post.

Once the brace post is in place, tighten the bolt on the brace band and cup to lock the post in place.

